

JIS10K

Nominal dia. (mm)	In. dia. (mm)	Out. dia. (mm)	Standard Conv.	Wall Thickness (t)	Pitch (q)	Conv. Height (w)	Spring Rate (N/mm per conv.)	Standard Length
50A	53.5	69.0	18	0.25/0.25	6	7.25	989	150
65A	67.0	82.5	16	0.25/0.25	8	7.25	1248	150
80A	78.5	96.5	16	0.25/0.25	8	8.5	893	150
100A	103.5	119.5	16	0.25/0.25	8	7.5	1600	150
125A	128.5	148.5	12	0.3/0.3	10	9.4	1765	150
150A	152.0	172.0	12	0.3/0.3	10	9.4	2016	150
200A	203.0	229.0	12	0.4/0.4	13	12.2	2885	200
250A	251.0	277.0	12	0.4/0.4	13	12.2	3516	200
300A	300.5	326.0	12	0.4/0.4	13	11.95	4385	200
350A	347.2	385.0	7	0.5/0.5	20	17.9	3074	200
400A	397.2	436.0	7	0.5/0.5	20	18.4	3202	200

JIS20K

Nominal dia. (mm)	In. dia. (mm)	Out. dia. (mm)	Standard Conv.	Wall Thickness (t)	Pitch (q)	Conv. Height (w)	Spring Rate (N/mm per conv.)	Standard Length
50A	53.5	70.5	7	0.4/0.3	10	7.8	2847	110
65A	67.0	86.0	6	0.4/0.3	11.5	8.8	2599	110
80A	78.5	100.5	6	0.4/0.5	12	10.1	3414	110
100A	103.5	126.5	7	0.4/0.5	14	10.6	3917	150
125A	128.5	153.5	7	0.45/0.6	14	11.45	5591	150
150A	152.0	180.5	6	0.45/0.6	15	13.2	4367	150
200A	203.0	233.0	8	0.5/0.6	16	13.9	5278	200
250A	251.0	285.0	8	0.6/0.7	16.5	15.7	7230	200
300A	300.5	336.5	7	0.7/0.7	19	16.6	8635	200